



XH₂O TM

Fortified with Menthol

◆ **Acidifier**

◆ **Biofilm Remover**

◆ **Water Sanitizer**

◆ **Descaler**

COMPOSITION:

Each 1000 ml contains

Benzalkonium Chloride Solution	6% v/v
Citric Acid	8% w/v
Menthol	0.2% w/v
Organic Acids	2% w/v
Inert Ingredients	Q.S.
Fortified by Menthol	

BENEFITS:

- Ultrafast acting with high residual effect.
- Non-corrosive
- Eco-friendly
- Balanceed pH & Synergistic action of ingredients.



APPLICATION GUIDELINES:

Calculate quantity of water required to fill pipelines (starting from tank outlets to endpoints) using following formulae or examples.

Total water required in liters = 0.77 X (radius of pipe in inches)² X total length of pipe in feet.

Diameter of pipe	Water holding capacity of 1ft pipe
0.5 inch	49 ml
0.75 inch	108 ml
1 inch	193 ml

- Empty water tank and pipeline completely and close all the ends. Fill the calculated quantity of water plus 10% extra in the water tank.
- Add XH₂O @25ml/ltr of water (if descaling in presence of Birds) or 50ml/ltr (in empty shed)
- Open water tank outlet and allow XH₂O treated water to flow through pipelines till its endpoint.
- Allow contact time of 3 hours and fill water tank with sanitized water.
- Open end caps and ensure the pipeline is flushed out with normal sanitized water from tank for 2-3 minutes.
- The pipeline is now descaled/sanitized for use.
- Continue with normal water treatment schedule.
- Perform descaling preferably during night hours.

PRECAUTIONS:

- Protect from direct light, do not mix with other chemicals.
- Store in cool and dry place. Keep out of reach of children.
- Wear suitable gloves and eyes/face protection.
- Concentrate solution. Use only after dilution.
- Avoid breathing spray mist.
- Avoid direct contact with skin, eyes and respiratory system.
- In case of contact with eyes rinse immediately with plenty of water. Seek medical advice.

DOSAGE:

Water Acidification & Sanitation: 1ml per 10 lit of Water.
Pipeline Descaling, Cleaning & Sanitation.
A. In presence of Birds: 25ml per liter of water.
B. Empty Shed: 50ml per liter of water.

Manufactured by:

Vetrix Nutrition Pvt. Ltd.

ISO 9001:2015 Certified Company

Plot No. 20, G.I.D.C., Opp. Gokul Oil Mill,
Near State Highway No. 41,
Siddhpur- 384151.
District: Patan, Gujarat.

TM- Trade Mark of Vetrix Nutrition Pvt. Ltd.



PRESENTATION:

5000 ml



Please contact us at:
Customer Care No. : +91 98909 42732
Email : info@vetrixnutrition.in